



RAMYAR SHIMI CO.

Chemicals For Petroleum Industries



ML 18 (Degreaser AP) ALL-PURPOSE DEGREASER FOR SHIPS , RIGS , AND SHIPYARDS

DESCRIPTION

Ramyar Shimi has specially formulated ML 18 to provide a cleaning system for as many marine applications as possible.

SAFE

ML 18 is safe on all metals, will not harm paint and will not harm personnel. It has a high flash point and is non-toxic.

USE

ML 18 is a blend of solvent cleaners and emulsifying agents that enable this product to be used in a number of applications. It can be used by applying with rag, mop, or spray . It can be used full strength or mixed with fresh or salt water. ML 18 can be applied and will rinse well with water or it can be wiped on and allowed to dry without a rinse. In areas where the only preparation required for painting is removing oil films. ML 18 can be wiped on. Wiped off and allowed to dry, (usually 15 minutes). And painted over.

ML 18 can be used for removing lube oils. Bunker C, heavy gear grease. Soils from bilge areas, deep tank cleaning. Spotting out decks. Tank tops, piers and docks.

DIRECTION

METAL CLEANING – GENERAL

ML 18 can be used straight or diluted with water according to the difficulty of the job. ML 18 can be applied by brushing. Wiping, or spraying at close range it can be flushed off with fresh or salt water.

Metal Cleaning - prior to painting

ML 18 can be used as a wipe – on cleaner prior to painting . It needs to be wiped dry.

MACHINERY AND EQUIPMENT

Use coarse spray or brush : wipe dry.

PRECAUTIONS

Avoid prolonged or repeated contact with the skin. Use in a well-ventilated area and keep away from open flames. See additional precautions on drum label.

SPECIFICATIONS

Form : A clear yellow liquid

Composition : A blend of selected solvents and emulsifiers

Flash point : 71 C.(160 F) C.O.C.

Stability : Stable after repeated freeze-thaw cycles

Weight : Approximately 0.79 kg per liter or 6.6 lbs. per U.S. gallon

