



RAMYAR SHIMI CO.

Chemicals For Petroleum Industries



ML 36 . DEGREASER TK LOW ODOR HEAVY – DUTY SOLVENT EMULSION CLEANER

DESCRIPTION

ML 36 . is a unique blend of low order solvents and emulsifiers formulated to clean heavy soils . Specially designed for cleaning and upgrading tankers , cleaning pump rooms and bilges . ML 36 . can be used to remove a variety of greases , oils and other organic soils . It is safe on all metals and coatings . It can be rinsed with either fresh or sea water .

ENGINE ROOM

Oil and grease accumulations on diesel engine exteriors , compressors , pumps and other machinery are quickly and easily removed with ML 36 . Spray or brush ML36. onto surfaces to be cleaned . Flush off with pressure stream of water .

TANK TOPS AND BULKHEADS

Hardened oil splatters and spills are effectively removed with ML 36 . applied by brush or spray . Let soak 15-30 minutes , then with pressure stream of water or with wet steam .

TANK CLEANING

Cargo tanks and deep tanks are easily cleaned with ML 36 . Spray directly on entire surface or introduce in Butterworth wash water .

Because of the high quantity of emulsifiers in ML 36 . , the bilge area and other areas that accumulate oil can be cleaned and rinsed freely .

GENERAL DEGREASING

ML 36 . can be used straight diluted with water according to severity of cleaning job . It can be applied by brushing , mopping , dipping or spraying . Allow ML36. to penetrate soil for 15-20 minutes . Rinse with fresh or sea water .

PRECAUTIONS

Avoid prolonged or repeated contact with skin . Use in well – ventilated area and keep away from open flame . See additional precautions on drum label .

SPECIFICATIONS

FROM : A clear , light amber liquid .

COMPOSITION : blend of selected solvents and emulsifiers .

FLASH POINT : 110 c . (230 F) C . 0 . C .

STABILITY : Stable after repeated freeze – thaw cycles .

